

MR-1, Mini Rocker-Shaker

DESCRIPTION

Mini Rocker-Shaker **MR-1** provides regulated gentle rocking motion of the platform and is ideal for mini gel destaining after electrophoresis, conducting Northern, Southern and Western blot analysis.

Shaker is a compact, noiseless device designed for personal use. Drive and brushless motor allow continuous mixing up to 7 days and ensures reliable, trouble-free operation for more than 2 years.

Non-slip, temperature resistant, silicone mat located on the rocker's platform provides a stable position for vessels during shaking. Optional dimpled PDM mat fixes tubes of different sizes.

The unit is designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40°C.

ACCESSORIES FOR THE STANDARD PLATFORM:

Optional dimpled mat **PDM** prevents different size tubes from rolling around the platform

Basic Plus Product Class



Rocking uni-rotation



Product video is available on the website

MR-12, Rocker-Shaker


DESCRIPTION

MR-12 Rocker-Shaker provides both soft and intensive mixing of solutions or nutrient media in vessels or plastic bags placed on the platform. Adjustable speed and platform tilt angle allows setting parameters for optimal solution transfer and mixing.

The device is ideal for gel destaining after electrophoresis and homogenisation of bioextraction media. It is optimal for biomolecule hybridisation on strips and staining/destaining procedures. When installed inside a bioincubator it is ideal for growing cells and cell cultures in disposable plastic reactor-bags (working volumes up to 10 litres, media volumes up to 5 litres).

The unit is designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40°C. Low voltage external power supply (12V) provides electrical safety in humid environment.

Premium Product Class



Rocking uni-rotation with adjustable tilt

MR-1 and MR-12, Rocker-Shakers

SPECIFICATIONS

	MR-1	MR-12
Mixing frequency range	1–30 oscill./min	1–99 oscill./min (increment 1 oscill./min)
Fixed tilt angle	7° (fixed)	0°–10° (increment 1°) (for 1–50 oscill./min) 10° (for 51–99 oscill./min)
Max. continuous operation time	168 h	
Digital time setting	1 min–24 h/non-stop	1 min–99 h 59 min (increment 1 min)/non-stop
Timer sound signal	—	yes
Non-slip silicone mat is supplied as standard	215 × 215 mm	480 × 380 mm
Maximum load	1 kg	5 kg
Display	LED	LCD, 2 × 16 signs
Platform working area	215 × 215 mm	480 × 380 mm
Overall dimensions (W×D×H)	220 × 205 × 120 mm	430 × 480 × 210 mm
Weight	2.1 kg	11.9 kg
Input current/power consumption	12 V, 320 mA/3.8 W	12 V, 1.1A/13 W
External power supply	Input AC 100–240 V, 50/60 Hz; Output DC 12 V	

PDM, dimpled mat



MR-1 with PDM dimpled mat



MR-12



ORDERING INFORMATION:

MR-1 with standard platform **Bio PP-4S**

MR-12 with standard platform **PP-480**

Optional accessories: for **MR-1**:

PDM, dimpled mat

Cat. number



BS-010152-AAG

BS-010130-AAI

PDM

3D, Sunflower Mini-Shaker

DESCRIPTION

"Sunflower" **3D** Mini-Shaker provides adjustable three-dimensional smooth rotation of the platform and is designed for mixing blood samples, minigel staining and destaining, sample washing, blot hybridisation reactions.

Mini-Shaker is a compact device with low energy consumption. The use of direct drive and brushless motor allows continuous mixing up to 7 days and ensures reliable, trouble-free operation for many years. Non-slip, temperature resistant, silicone mat located on the shaker's platform provides a stable position for vessels during shaking. The platform is suitable for placing a versatile dimpled PDM mat for different size tubes.

Mini-Shaker can be used in cold rooms or incubators, operating at ambient temperature range +4°C to +40°C.

Basic Plus Product Class



3D — uni-rotation



Product video is available on the website

Multi Bio 3D, Programmable mini-shaker («Sunflower» type)

DESCRIPTION

Programmable mini-shaker **Multi Bio 3D** is designed for various applications: hybridization reactions, cell growing, gel washing, soft extraction and homogenisation of biological components in solutions.

Multi Bio 3D provides realization of several types of motion in one module. This option of Biosan instruments essentially extends possibilities and enhances the efficiency of preparation of test samples as well as allows selecting the mixing type according to individual requirements.


Microprocessor control allows performing **1 Orbital 3D rotation** of the platform and but also **2 Reciprocal 3D motion** (of ping-pong type) and **3 Soft vibrating rocking**. These three motion types can be performed separately, pairwise and in cycles, periodically repeating the sequence of three motion types. The shaker is designed for laboratories with increased demands for the quality of mixing, extraction and cell growing processes.

Non-slip, temperature resistant, silicone mat located on the shaker platform provides a stable position for vessels during shaking. Optional dimpled PDM mat fixes tubes of different sizes.

Programmable shaker can be used in cold rooms or incubators, operating at the ambient temperature range +4°C to +40°C.

Premium Product Class

Ø 22 mm orbit



Multi-rotation



Product video is available on the website

3D Mini-Shaker and Multi Bio 3D,
Programmable 3D shaker («Sunflower» type)

	3D	Multi Bio 3D
❶ Speed control range (orbital and reciprocal motion)	5–60 rpm	1–100 rpm
❷ Turning angle (reciprocal motion)	—	0–360° (increment 30°)
❸ Rocking angle (vibro motion)	—	0–5° (increment 1°)
Fixed tilt angle	7°	
Orbit	—	22 mm
Platform working area	215 × 215 mm	
Non-slip silicone mat is supplied as standard		
Maximum continuous operation time	168 h	24 h
Time setting range for ❶ ❷	—	0–250 s
Time setting range for ❸	—	0–5 s
Number of cycles	—	0–125 times
Timer sound signal	—	yes
Maximum load	1 kg	
Overall dimensions (W × D × H)	235 × 235 × 140 mm	
Weight	1.2 kg	1.8 kg
Input current/power consumption	12 V, 260 mA/3.1 W	12 V, 380 mA/4.6 W
External power supply	Input AC 100–240 V, 50/60 Hz; Output DC 12 V	

Accessories for the standard platform:

Optional dimpled mat PDM prevents different size tubes from rolling around the platform

PDM, dimpled mat



Multi Bio 3D with PDM mat



ORDERING INFORMATION:

3D with stand, platform Bio PP-4S
Multi Bio 3D with stand, platform Bio PP-4S

Optional accessories:

PDM dimpled mat

Cat. number 

BS-010151-AAG
BS-010125-AAG

PDM

PSU-10i, Orbital Shaker

DESCRIPTION

Shaker **PSU-10i** provides regulated orbital motion of the platform and is designed for use both in small specialized biotechnological laboratories and in large multidisciplinary laboratories: a choice of five (5) interchangeable platforms provides the possibility of performing various procedures and techniques.

Shaker **PSU-10i** incorporates a direct drive system, a brushless motor with a guaranteed service life of up to 35,000 hours and an automatic loading balancing system. These innovations allow for continuous mixing up to 7 days, ensure reliable, trouble-free operation for more than 2 years and significantly expand the device performance range in both high and low limits.

The unit is designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40°C.

Premium
Product Class

Ø 10 mm
orbit



Product video is available on the website

PSU-20i, Orbital Shaker

DESCRIPTION

Shaker **PSU-20i** provides three motion types: **1 Orbital**, **2 Reciprocal** and **3 Vibrating**, which can be performed separately, pairwise and sequentially in repeated cycles.

Shaker is designed for applications both in small specialized laboratories and in large multidisciplinary laboratories. **PSU-20i** is an ideal instrument for laboratories researching biopharmaceutics and biomedicine.


Shaker **PSU-20i** is noiseless and reliable in operation, incorporates a direct drive system and brushless motor with a guaranteed service life up to 35,000 working hours. Direct drive and brushless motor allows for continuous mixing for up to 7 days and ensures reliable operation for more than two years.

A choice of nine different interchangeable platforms provides the possibility of performing various procedures and techniques. Special attention should be paid to a multilevel platform, which allows accommodation of a large number of various microplates, Petri dishes, cultural bags and other low containers.

The unit is designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40°C.

Premium
Product Class

Ø 20 mm
orbit



Multi-motion

Description and pictures of all platforms can be found on page 22-23


PSU-10i and PSU-20i, Orbital Shakers

SPECIFICATIONS


	PSU-10i	PSU-20i
Multi-motion	—	yes
Speed control range*	50–450* rpm (increment 10 rpm)	20–250* rpm (increment 5 rpm)
Digital speed control	yes	
Max. continuous operation time	168 h	
Orbit	10 mm	20 mm
Digital time setting	1 min–96 h/non-stop	
Timer sound signal	yes	
Maximum load	3 kg	8 kg
Overall dimensions (WxDxH)	255 × 255 × 100 mm	410 × 410 × 130 mm
Weight	3.4 kg	11.7 kg
Input current/power consumption	12 V, 800 mA/9.6 W	12 V, 3.2 A/40 W
External power supply	Input AC 100–240 V, 50/60 Hz; Output DC 12 V	

* — max. speed depends on the load and vessels' shape

Platform P-6/250 for PSU-10i



Platform Bio PP-4 for PSU-10i



Platform for PSU-20i PP-20/4



Platform Bio PP-4 for PSU-10i



ORDERING INFORMATION:




Cat. number 

PSU-10i, Shaker without platform

BS-010144-AAN

PSU-20i, Shaker without platform








BS-010145-ACI

PSU-20i motion types	Description	Speed range	Turning angle	Motion timer*	Digital time setting
1  Orbital	Orbital motion with an option of shifting direction	20–250 rpm	—	0–250 s	1 min–96 h (increment 1 min) or non-stop
2  Reciprocal	Orbital motion with shifting direction of rotation	20–250 rpm	0–360° (30° increment)	0–250 s	
3  Vibrating	High speed, low amplitude motion	—	0–5° (1° increment)	0–5 s	

* — for switching to the next motion in the cycle

Description and pictures of all platforms can be found on page 22-23

Platforms for PSU-10i and ES-20

Platform	Description	Dimensions (Working area)	Cat. number
UP-12 Used on PSU-10i, ES-20	 Universal platform with adjustable bars for different types of flasks, bottles and beakers with silicone mat	285 × 220 × 40 mm (270 × 185 × 40 mm)	BS-010108-AK
Bio PP-4 Used on PSU-10i	 Flat platform with silicone mat for Petri dishes, culture flasks, agglutination cards	255 × 255 mm (230 × 230 mm)	BS-010116-AK
PP-4 Used on ES-20, PSU-10i	 Metallic flat platform with silicone mat for Petri dishes, culture flasks, agglutination cards	220 × 220 mm (215 × 215 mm)	BS-010108-BK
NEW SPM	 Double-sided adhesive mat as an alternative for regular flask clamps (for PP-4)	220 × 220 mm (1 per platform)	BS-010111-BK
P-12/100 Used on PSU-10i, ES-20	 Platform with clamps for flasks, 100–150 ml (12 places)	250 × 190 mm (250 × 190 mm)	BS-010108-EK
P-6/250 Used on PSU-10i, ES-20	 Platform with clamps for flasks, 250–300 ml (6 places)	250 × 190 mm (250 × 190 mm)	BS-010108-DK
P-16/88 Used on PSU-10i, ES-20	 Platform with spring holders for up to 88 tubes up to 30 mm diameter (e. g. 10 ml, 15 ml, 50 ml tubes)	275 × 205 × 75 mm (275 × 205 × 75 mm)	BS-010116-BK

SPML, SPM, Double-sided adhesive strips and mat NEW

DESCRIPTION

Convenient alternative to traditional steel holders, an easy way to fix tubes, plates, flasks and other laboratory wares on platforms for cultivation, incubation and mixing. Two size options are offered **SPML** can be used with UP-168 platform on Biosan orbital shaker PSU-20i and in ES 20/80, ES 20/60 orbital shakers.

SPM is compatible with PP-4 platform, which fits both on PSU-10i orbital shaker and in ES-20 Shaker-Incubator.

Made of polyurethane with adhesive, simple to clean and durable, able to withstand up to 1,000 times placement/removal or 12 months of use. Additional information about temperature, working volume and speed limitations available in the user manual.

SPECIFICATIONS

SPML Size (L×W×H)	390 × 80 × 3 mm (double sided 1.5 mm PU with PET adhesive)
SPM Size (L×W×H)	210 × 210 × 3 mm (double sided 1.5 mm PU with PET adhesive)
Colour	transparent
Duration of use	up to 1,000 times placement/removal or 12 months
Temperature range	+4C° to +80C°
Shaking speed	0–300 rpm

SPM on PP-4 platform



SPML on UP-168 platform








ORDERING INFORMATION:

- SPM**, Double-sided adhesive mat
- SPML**, Set of 3 double-sided adhesive strips


Cat. number

- BS-010111-BK
- BS-010135-MK

Platforms for PSU-20i and ES-20/60

Platform	Description	Dimensions (Working area)	Cat. number
UP-330 Used on PSU-20i	 Universal platform with adjustable bars for different types of flasks, beakers	345 × 430 × 105 mm (300 × 400 × 80 mm)	BS-010145-AK
P-30/100 Used on PSU-20i, ES-20/60	 Platform with 30 clamps for 100–150 ml flasks	360 × 400 mm (360 × 400 mm)	BS-010135-BK
P-16/250 Used on PSU-20i, ES-20/60	 Platform with 16 clamps for 250–300 ml flasks	360 × 400 mm (360 × 400 mm)	BS-010135-CK
P-9/500 Used on PSU-20i, ES-20/60	 Platform with 9 clamps for 500 ml flasks	360 × 400 mm (360 × 400 mm)	BS-010135-AK
P-6/1000 Used on PSU-20i, ES-20/60	 Platform with 6 clamps for 1,000 ml flasks	360 × 400 mm (360 × 400 mm)	BS-010135-DK
PP-400 Used on PSU-20i, ES-20/60, ES-20/80	 Flat platform with non-slip silicone mat	360 × 400 mm (360 × 400 mm)	BS-010135-FK
UP-168 Used on ES-20/60, ES-20/8	 Universal platform for different flasks (Clamps ordered separately)	360 × 400 mm (360 × 400 mm)	BS-010135-JK
FC-50 FC-100 FC-250 FC-500 FC-1000 FC-2000 used on PSU-20i	 Clamp for 50, 100, 250, 500, 1000, 2,000 ml flask (for UP-168)	Ø 50 mm Ø 65 mm Ø 85 mm Ø 105 mm Ø 130 mm Ø 165 mm	BS-010126-MK BS-010126-HK BS-010126-JK BS-010126-LK BS-010126-IK BS-010126-NK
NEW SPML	 Set of 3 double-sided adhesive strips as an alternative for regular flask clamps (for UP-168)	390 × 80 × 3 mm (3 per platform)	BS-010135-MK
TR-21/50	 Test tube rack for 50 ml with 21 drillings (for UP-168)	340 × 124 mm (2 per platform)	BS-010135-KK
TR-44/15	 Test tube rack for 15 ml with 44 drillings (for UP-168)	340 × 124 mm (2 per platform)	BS-010135-LK
PP-20/4 Used on PSU-20i	 Four-level flat platform with non-slip rubber mat	380 × 480 × 510 mm (365 × 465 × 510 mm)	BS-010126-EK
PP-20/3 Used on PSU-20i	 Three-level flat platform with non-slip rubber mat	380 × 480 × 340 mm (365 × 465 × 340 mm)	BS-010126-DK
PP-20/2 Used on PSU-20i	 Two-level flat platform with non-slip rubber mat	380 × 480 × 170 mm (65 × 465 × 170 mm)	BS-010126-CK
PP-20 Used on PSU-20i	 One-level flat platform with non-slip rubber mat	380 × 480 mm (365 × 465 mm)	BS-010126-BK

MPS-1, High-Speed Multi Plate Shaker



DESCRIPTION

High-Speed Multi Plate Shaker **MPS-1** can be used in virtually any application by providing adjustable mixing of reagents in microtest plates, PCR plates, deepwell plates and test tubes (shaking tubes 0.2 to 2 ml and vortexing any volume up to 50 ml).

The shaker is compact and user-friendly. The shaker is ideal for personal use.

MPS-1 features a head for vortexing a single tube. The unit is designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C, decreasing linearly to 50% relative humidity at 40°C. Low voltage external power supply (12 V) provides electrical safety in a humid environment.

MPS-1 features **Pulse Mode** mixing function that works on the principle of giving a periodic impulse: the tube is accelerated to the set speed, holds it for 3 seconds and then drops the speed to zero. This motion is repeated until the timer runs out. This method provides a constant state particle resuspension inside a tube, as the acceleration is always changing. The advantage of this method is the high throughput of mixed samples compared to vortexing a single tube.

Features

- Speed control range 300–3,200 rpm
- Stable mixing with 3 mm orbit
- Five mixing presets
- **Pulse Mode** mixing function
- Quiet operation — low noise at maximum speed
- Universal platform holder for Deepwell plates and Microtest plates
- Additional four platforms for semiskirted and unskirted PCR plates 200 µl as well as for tubes from 0.2 to 2 ml

Platform for semi-/unskirted PCR plate 200 µl

Platform for 24 tubes 1.5–2 ml



Product video is available on the website

MPS-1, High-Speed Multi Plate Shaker

SPECIFICATIONS

Vortexing a 50 ml tube



Vortexing a 15 ml tube



Deepwell plate 96/1000 µl



Microtest plate 200 µl



Deepwell plate 96/500 µl



Mixing Speed control range	300–3,200 rpm
----------------------------	---------------

Platform options:

- | | |
|---|---------|
| – For semi-/unskirted PCR plate or 96 microtest tubes 0.2 ml | P-02/96 |
| – For 24 microtest tubes 1.5–2 ml | P-2/24 |
| – For 32 microtest tubes 0.5 ml | P-05/32 |
| – For 24 microtest tubes 0.5 ml and 48 microtest tubes 0.2 ml | P-02/05 |
| – Universal platform for deepwell plates, 96-well microtest plates (U, V or flat bottomed), 384-well microtest plates | |

Types of mixing presets:

VORTEX	3,200 rpm
HARD	2,600 rpm
MEDIUM	1,800 rpm
SOFT	1,000 rpm
CUSTOM	adjustable rpm

Features a **Pulse Mode** mixing function

Features a Vortex function

Maximum load	0.3 kg
Mixing Orbit	3 mm
Acceleration time to maximum speed	5 s
Digital time setting	0–60 min (15 s increment)/non-stop
Timer sound signal	yes
Maximum continuous operation time	8 h
Noise level, not more	65 dB
Weight	5.1 kg
Overall dimensions (W×D×H)	225 × 215 × 150 mm
Input current/power consumption	12 V, 800 mA / 10 W
External power supply	Input AC 100–240 V 50/60 Hz; Output DC 12 V

ORDERING INFORMATION:

Cat. number 

MPS-1 , Multi Plate Shaker with built-in universal platform	BS-010216-A03
MPS-1 , Multi Plate Shaker with built-in universal platform and set of 4 platforms (P-02/96, P-2/24, P-05/32, P-02/05)	BS-010216-A11

Optional platforms:

Cat. number

❶ P-02/96	For semi-/unskirted PCR plate or 96 microtest tubes 0.2 ml	BS-010216-CK
❷ P-2/24	For 24 microtest tubes 1.5–2 ml	BS-010216-AK
❸ P-05/32	For 32 microtest tubes 0.5 ml	BS-010216-BK
❹ P-02/05	For 24 microtest tubes 0.5 ml and 48 microtest tubes 0.2 ml	BS-010216-DK

❶ Platform P-02/96



❷ Platform P-2/24



❸ Platform P-05/32



❹ Platform P-02/05



PSU-2T, Mini-Shaker

DESCRIPTION

Mini-Shaker **PSU-2T** is designed for immunoassays and provides adjustable mixing of reagents in microplates. The device ensures smooth movement of the platform even at low speeds.

Shaker is a compact and user-friendly device. It takes up little space on a desk and is ideal for personal use. Direct drive and brushless motor allow continuous mixing up to 7 days and ensures reliable, trouble-free operation for more than 2 years. Display of the device switches between time and speed readings.

The unit is designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40°C.

SPECIFICATIONS

Speed control range	150–1,200 rpm
Digital time setting	1 min–24 h/non-stop
Digital setting and control of time and speed	
Max. continuous operation time	168 h
Direct drive mechanism	
Orbit	2 mm
Overall dimensions (W×D×H)	220 × 205 × 90 mm
Weight	2 kg
Input current/ power consumption	12 V, 280 mA/3.4 W
External power supply	Input AC 100–240 V, 50/60 Hz; Output DC 12 V

ORDERING INFORMATION:

Cat. number

PSU-2T with standard platform **IPP-2** **BS-010155-AAG**

Optional platforms

IPP-4 BS-010102-AK




Product video is available
on the website

A Platform IPP-2



B Platform IPP-4



Platforms for microtest plates:

A IPP-2 (standard platform) 184 × 132 mm
for 2 microtest plates

B IPP-4 (optional platform) 266 × 170 mm
for 4 microtest plates



Multi Bio RS-24 and Multi RS-60, rotators



Multi Bio RS-24



Product video is available on the website



Multi RS-60




Product video is available on the website

It is possible to choose the position of tubes for rocking motion – horizontal or vertical. The platform does not make an additional revolution before stopping in the horizontal plane.

Programmable Rotators perform several motion types in one module. Microprocessor control allows performing not only **1 Vertical overhead rotation** of the platform, but also **2 Reciprocal rotation (rocking motion)** as well as **3 Vibration**. These three motion types can be performed separately, pairwise and in cycles, periodically repeating the sequence of three motion types. Multi-Rotation option of Biosan instruments substantially expands possibilities and enhances the efficiency of sample preparation for the examined materials and allows adjusting the mixing procedure according to the individual tasks.

Programmable Rotators can be used for a variety of applications in modern life science laboratories: for hybridisation reactions, cell growing, soft extraction and homogenisation of biological components in solutions, as well as for reactions of binding and washing of magnetic particles.

Multi Bio RS-24 and **Multi RS-60** are designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40 °C. Low voltage external power supply (12 V / 24V) provides electrical safety in a humid environment.



Programmable Rotator provides 3 rotation types and Pause:

- 1** Vertical overhead rotation
- 2** Reciprocal rotation (rocking motion)
- 3** Vibro
- P** Pause

Multi Bio RS-24 and Multi RS-60, rotator

SPECIFICATIONS

Multi Bio RS-24		Multi RS-60
❶ Vertical overhead rotation:		
Speed control range	1–100 rpm (increment 1 rpm)	
Vertical rotation movement	360°	
Time setting range	0–250 s	
❷ Reciprocal rotation (rocking motion):		
Speed control range	1–100 rpm (increment 1 rpm)	
Tilt angle range	1–90° (increment 1°)	
Time setting range	0–250 s	
❸ Vibro:		
Tilt angle range	0–5° (increment 1°)	
Pause/Vibro time setting range	0–5 s	
GENERAL SPECIFICATIONS:		
Digital time setting	1 min–24 h/non-stop (increment 1 min)	
Timer sound signal	yes	
Maximum load	0.5 kg	0.8 kg
Overall dimensions (W×D×H)	365 × 195 × 155 mm	430 × 230 × 230 mm
Weight	1.7 kg	3.8 kg
Input current/power consumption	12 V, 660 mA/8 W	24 V, 750 mA/18 W
External power supply	Input AC 100–240 V, 50/60 Hz; Output DC 12 V	Input AC 100–240 V, 50/60 Hz; Output DC 24 V

Multi Bio RS-24 with optional platform PRSC-22



Multi RS-60 with standard platform PRS-48



ORDERING INFORMATION:

Cat. number

Multi Bio RS-24 with standard platform PRS-26	BS-010117-AAG
Multi RS-60 with standard platform PRS-48	BS-010118-AAI
Optional platforms for Multi Bio RS-24:	
PRS-5/12	BS-010117-HK
PRS-10	BS-010117-IK
PRSC-22	BS-010117-LK
PRSC-10	BS-010117-JK
PRS-1DP	BS-010149-DK
M-8/50	BS-010117-PK
Optional platforms for Multi RS-60:	
PRS-8/22	BS-010118-AK
PRS-14	BS-010118-BK

Description and pictures of all platforms can be found on page 29



Platforms for Multi Bio RS-24

Standard:	Capacity	Tube Volume	Tube Diameter	Cat. number
1 PRS-26	26	1.5–15 ml	10–16 mm	BS-010117-GK
Optional				
2 PRS-5/12	5 and 12	up to 50 and 1.5–15 ml	20–30 and 10–16 mm	BS-010117-HK
3 PRS-10	10	up to 50 ml	20–30 mm	BS-010117-IK
4 PRSC-22	22	15 ml	16 mm	BS-010117-LK
5 PRSC-10	10	50 ml	25–30 mm	BS-010117-JK
6 M-8/50	8	50 ml	25–30 mm	BS-010117-PK
7 PRS-1DP	Platform for microplates and racks for tall tubes 0.5 and 1 ml (e.g. Thermo 3741MTX, 3742MTX, 3744MTX)			BS-010149-DK

1 PRS-26



2 PRS-5/12



3 PRS-10



4 PRSC-22



5 PRSC-10



6 M-8/50



7 PRS-1DP



Clamps on PRSC-10



PRS series platforms are equipped with universal rubber clamps for different size tube fixation;
PRSC series platforms have metal clamps able to hold heavier solutions (e.g. soil, sand).

Platforms for Multi RS-60

Standard:	Capacity	Tube Volume	Tube Diameter	Cat. number
1 PRS-48	48	1.5–15 ml	10–16 mm	BS-010118-CK
Optional:				
2 PRS-8/22	8 and 22	up to 50 and 1.5–15 ml	20–30 and 10–16 mm	BS-010118-AK
3 PRS-14	14	up to 50 ml	20–30 mm	BS-010118-BK

1 PRS-48



2 PRS-8/22



3 PRS-14



Bio RS-24, Mini-Rotator

DESCRIPTION

Mini-rotator **Bio RS-24** provides vertical rotation of the platform. The rotator is an ideal instrument for preventing blood coagulation in tubes and fulfilling of procedures of biological components extraction.

The device is simple to operate; it is designed as a low-cost solution.

The unit is designed for operation in cold rooms, incubators (excluding CO₂ incubators) and closed laboratory rooms at ambient temperature from +4°C to +40°C in a non-condensing atmosphere and maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40°C. Low voltage external power supply (12 V) provides electrical safety in a humid environment.

SPECIFICATIONS

Speed control range	5–30 rpm
Vertical rotation movement	overhead, 360°
Digital time setting	1 min–24 h/non-stop (increment 1 min)
Timer sound signal	yes
Maximum continuous operation time	8 h
Overall dimensions (W×D×H)	325 × 190 × 155 mm
Weight	1.4 kg
Recommended load	75% of the rated volume
Input current/power consumption	12 V, 110 mA/1.3 W
External power supply	Input AC 100–240 V 50/60 Hz; Output DC 12 V

PRS series platforms are equipped with universal rubber clamps for different size tube fixation;

PRSC series platforms have metal clamps able to hold heavier solutions (e.g. soil, sand).

Basic Plus

Product Class



Bio RS-24 in operation



Vertical rotation 360°

ORDERING INFORMATION:

Cat. number

Bio RS-24	
with standard platform PRS-22	BS-010133-AAG
Optional platforms:	
PRS-4/12	BS-010117-AK
PRSC-18	BS-010117-EK

Platform	Capacity	Tube Volume	Tube Diameter, Ø
1 PRS-22 (standard)	22	1.5–15 ml	10–16 mm
2 PRS-4/12 (optional)	4 and 12	up to 50 and 1.5–15 ml	20–30 mm and 10–16 mm
3 PRSC-18 (optional)	18	15 ml	16 mm

1 PRS-22



2 PRS-4/12




3 PRSC-18



Basic Plus

Product Class



Basic Plus

Product Class



V-1 plus and V-32, Vortexes

V-1 plus vortex and **V-32** multi vortex are intended for intensive mixing of samples in tubes with an eccentric mechanism.

Vortex can be used for different operations:

- Mixing tissue samples;
- Suspending cell samples;
- Mixing chemical samples;
- Mixing bacterial and yeast cells when washing from the culture medium;
- Extracting metabolites and enzymes from cells and cell cultures, etc.

Vortex can be used to perform various DNA/RNA operations, such as purification of low-molecular DNA/RNA fragments in PCR-diagnostics.

Vortex is applicable in all the fields of laboratory research in biotechnology, microbiology and medicine.

Vortexes have two operation modes:

- Continuous operation;
- Impulse operation. (**V1 plus** pressure activated)

Model **V-1 plus** is a personal vortex with a fluoroplastic head for single tube vortexing.

Model **V-32** is a universal vortex multipurpose device with different accessories. It is supplied with a 32-socket universal platform PV-32 for Eppendorf type tubes up to 1,5 ml (1.5/0.5/0.2 ml–16/8/8 sockets) and a PL-1 head for vortexing a single tube up to 50 ml. An optional 6-socket platform PV-6/10 for 10 ml tubes (maximum tube diameter 15 mm) or a platform PV-48 for six strips of eight 0.2 ml microtubes can be supplied on request.



Product video is available on the website

Platform PL-1 for V-32



V-1 plus and V-32, Vortexes

SPECIFICATIONS

	V-1 plus	V-32
Mixing principle	Vibro Eccentric	
Speed control range	500–3,000 rpm	
Acceleration time	<1 s	3 s
Maximum continuous operation time	24 h	
Timer sound signal	—	
Mixing module for tubes	from 0.2 to 50 ml	from 0.2 to 10 ml
Maximum mixing volume	30 ml	45 ml
Maximum load	30 g	70 g
Orbit	4 mm	2 mm
Dimensions (W×D×H)	90 × 150 × 80 mm	120 × 180 × 100 mm
Weight	0.8 kg	1.5 kg
Input current/power consumption	12 V, 320 mA/3.8 W	
External power supply	Input AC 100–240 V, 50/60 Hz; Output DC 12 V	

V-1 Plus



V-1 Plus




V-1 Plus



Platform PV-6/10 for V-32



Platform PV-48 for V-32



V-32 with platform PV-48



ORDERING INFORMATION:

V-1 plus

Cat. number

BS-010203-AAG

V-32 with standard platforms **PL-1** and **PV-32**

BS-010207-AAG

Optional platforms for V-32:

PV-6/10 platform for 6–10 ml tubes (max. Ø 15 mm)

BS-010207-BK

PV-48, platform for 6–8 × 0.2ml strips or 48 tubes of 0.2 ml

BS-010207-GK

Basic Plus

Product Class

MSV-3500 with platform
SV-8/15



Product video is available
on the website

MSV-3500, Multi Speed Vortex

Multi Speed Vortex **MSV-3500** is designed for soft or intensive mixing of reagents in different size and type plastic tubes (0.2 to 50 ml).

It is designed for operation in life science laboratories working in biochemistry, cell and molecular biology.

Unit has four types of interchangeable platforms: for Eppendorf type microtest tubes, 10/15/50 ml tubes (diameter 12/16/30 mm). Platforms can be ordered separately or as one set with **MSV-3500**.

Speed and time are under microprocessor control. LCD display indicates two lines of values: the set and actual values of speed and time.

Unit provides high maximum speed of platform rotation efficiently mixing microvolumes (less than 5 µl) of samples.

Speed control range	300–3,500* rpm
Digital time setting	0–60 min/non-stop (increment 1 min)
Timer sound signal	yes
Display	LCD, 2 × 16 signs
Orbit	4 mm
Maximum load	0.2 kg
Maximum continuous operation time	8 h
Dimensions (WxDxH)	180 × 170 × 145 mm
Weight	2.6 kg
Input current/power consumption	12 V, 1 A / 12 W
External power supply	Input AC 100–240 V, 50/60 Hz, Output DC 12 V

* — Maximum speed depends on load

ORDERING INFORMATION:	Cat. number
MSV-3500 with all platforms	BS-010210-TAH
MSV-3500 without platform	BS-010210-AAH

Optional platforms:		Cat. number
1 SV-16/8	Platform for 16 × 1.5 ml + 8 × 0.5 ml + 8 × 0.2 ml microtubes, Ø 11/8/6 mm	BS-010210-CK
2 SV-10/10	Platform for 10 × 10 ml tubes 12 mm diameter	BS-010210-BK
3 SV-8/15	Platform for 8 × 15 ml tubes 16 mm diameter	BS-010210-DK
4 SV-4/30	Platform for 4 × 50 ml tubes 30 mm diameter	BS-010210-AK



RCP-24, Homogenizer

ANNOUNCEMENT

DESCRIPTION

Reciprocal Homogenizer **RCP-24**, a bench-top mechanical device designed for mixing, grinding, homogenizing and emulsifying biological objects in microtubes by vigorously mixing by reciprocal motion with various beads for sample preparation for subsequent academic, pharmaceutical, biotechnological or biomedical studies. Homogenizer facilitates the formation of a supernatant containing nucleic acids and proteins suitable for subsequent purification, extraction or analysis. The device is optimized for extracting proteins, DNA, RNA or tRNA from various tissue sources, but it can also be used for other applications. **RCP-24** performs efficient homogenization of mammalian tissue, plant tissue or other biomaterials.

SPECIFICATIONS

Test tubes capacity	up to 24
Test tubes	2 ml
Speed control range	100–2,000 rpm (increment 100 rpm)
Digital time setting	1–15 min (increment 1 min)
Oscillation amplitude	44 mm, vertical
Dimension (WxDxH)	285 × 400 × 440 mm
Input current / power consumption	230 V, 50 Hz/ 220 W (1.3 A)
Weight	19.1 kg

Basic Plus

Product Class

